

ZF W103100 NC

Vertical offset, remote mount marine transmission.

Description

- Marine reduction transmission series for heavy duty, commercial application comprising:NC:Direct Drive Reduction (without clutch) .
- Robust design also withstands continuous duty in workboat applications .
- Fully works tested, reliable and simple to install .
- Compatible with all types of engines and propulsion systems .
- Design, manufacture and quality control standards comply with ISO 9001 .
- Easy onboard maintenance .

Features

- Robust, torsion - resistant housing (cast iron/welded steel) .
- Case hardened and precisely ground gear teeth for long life and smooth running .
- Input- and output shafts mounted in plain bearings .
- Output shaft thrust bearing designed to take maximum propeller thrust .
- Free standing .
- Cast-on brackets .
- Oil cooler complete with fittings .

Options

- Engine-matched torsional coupling .
- Standard monitoring system .
- Special monitoring (acc. Classification Society requirements) .
- PTO (live or clutchable) .
- Standby oil pump .
- Classification by all major Classification Societies on request .



ZF W103100 NC

Ratings

Continuous Duty


RATIOS	MAX. TORQUE		POWER/RPM		INPUT POWER CAPACITY						MAX. RPM
	Nm	ftlb	kW	hp	400 rpm		428 rpm		500 rpm		
					kW	hp	kW	hp	kW	hp	
2.417	229200	169049	24.0000	32.1845	9600	12874	10272	13775	12000	16092	500
3.231	217110	160132	22.7340	30.4868	9094	12195	9730	13048	11367	15243	500
3.583	198640	146509	20.8000	27.8933	8320	11157	8902	11938	10400	13947	500
3.929	186139	137289	19.4910	26.1379	7796	10455	8342	11187	9745	13069	500
4.238	173810	128196	18.2000	24.4066	7280	9763	7790	10446	9100	12203	500
4.750	151368	111643	15.8501	21.2553	6340	8502	6784	9097	7925	10628	500
5.150	134454	99168	14.0790	18.8802	5632	7552	6026	8081	7039	9440	500

* Special Order Ratio.
 Ratings shown for the ZF W17000, and larger gearboxes, are valid for applications without ice classification and comply with BV (Bureau Veritas) rules.



ZF W103100 NC

Dimensions



mm (inches)							
A	B ₁	B ₂	H ₁	H ₂	L	L ₁	L ₂
1,120 (44.1)	1,375 (54.1)	1,375 (54.1)	1,340 (52.7)	1,810 (71.3)	1,840 (72.4)	2,190 (86.2)	425 (16.7)
Weight kg (lb)				Oil Capacity Litre (US qt)			
27,000 (57,200)				1,050 (1,113)			




ZF W103100 NC


PTO

PTO Configurations


PTO3 (Live)



PTO4 (Clutchable)



PTO5 (Live)



Duty Definitions

CONTINUOUS DUTY DEFINITION Continuous operation with little or no variations in engine speed and power

Average engine operating hours limit: **Unlimited**

Typical hull forms: **Displacement.**

Typical applications: **Heavy duty commercial vessels, tugs, fishing boats.**

Duty Ratings

Ratings apply to marine diesel engines at the indicated speeds. At other engine speeds, the respective power capacity (kW) of the transmission can be obtained by multiplying the Power/Speed ratio by the speed.

Approximate conversion factors:

1 kW = 1.36 metric hp

1 kW = 1.34 U.S. hp (SAE)

1 U.S. hp = 1.014 metric hp

1 Nm = 0.74 lb.ft.

Ratings apply to right hand turning engines, i.e. engines having counterclockwise rotating flywheels when viewing the flywheel end of the engine. These ratings allow full power through forward and reverse gear trains, unless otherwise stated.

Contact your nearest ZF Sales and Service office for ratings applicable to gas turbines, gasoline (petrol) engines, as well as left hand turning engines, and marine transmissions for large horsepower capacity engines.

Ratings apply to marine transmissions currently in production or in development and are subject to change without prior notice.

NOTE: THE MAXIMUM RATED INPUT POWER MUST NOT BE EXCEEDED (SEE RESPECTIVE RATINGS IN THE TECHNICAL DATA SHEETS)

Safe Operating Notice

The safe operation of ZF products depends upon adherence to technical data presented in our brochures. Safe operation also depends upon proper installation, operation and routine maintenance and inspection under prevailing conditions and recommendations set forth by ZF. Damage to transmission caused by repeated or continuous emergency manoeuvres or abnormal operation is not covered under warranty. It is the responsibility of users and not ZF to provide and install guards and safety devices, which may be required by recognized safety standards of the respective country (e.g. for U.S.A. the Occupational Safety Act of 1970 and its subsequent provisions).

Monitoring Notice

The safe operation of ZF products depends upon adherence to ZF monitoring recommendations presented in our operating manuals, etc. It is the responsibility of users and not ZF to provide and install monitoring devices and safety interlock systems as may be deemed prudent by ZF. Consult ZF for details and recommendations.

Torsional Responsibility and Torsional Couplings

The responsibility for ensuring torsional compatibility rests with the assembler of the drive and driven equipment. ZF can accept no liability for gearbox noise caused by vibrations or for damage to the gearbox, the flexible coupling or to other parts of the drive unit caused by this kind of vibration. Contact ZF for further information and assistance. ZF recommends the use of a torsional limit stop for single engine powered boats, wherein loss of propulsion power can result in loss of control. It is the buyer's responsibility to specify this option, which can result in additional cost and a possible increase in installation length.

ZF can accept no liability for personal injury, loss of life, or damage or loss of property due to the failure of the buyer to specify a torsional limit stop. ZF selects torsional couplings on the basis of nominal input torque ratings and commonly accepted rated engine governed speeds. Consult ZF for details concerning speed limits of standard offering torsional couplings, which can be less than the transmission limit. Special torsional couplings may be required for Survey Society Ice Classification requirements.